

PTPW Series

Spiral Wrap is a high-density polyethylene (HDPE) protective spiral wrap designed specifically for heavy-duty bundling and protection of hydraulic and pneumatic hoses used across various industries.

- The spiral wrap is UV resistant and can handle extreme temperatures from -40° F through 280° F.
- It serves as a cost effective and quick method for minimizing heavy production losses.
- It protects against losses and damages caused by depreciation, abrasion, regular misuse, poor maintenance or severe working environments.
- Finally, the wraps round beveled edges allow for safe and easy installation.

Material: High-Density Polyethylene

Standard Colour: Black, Blue, Yellow & Red

When Ordering:

1. Select your part number 2. Select the roll size 3. Select your colour

Combine these 3 elements to get a part number you can order with by adding together:

Part number + Roll Size + Colour Code (BLK, RED, YEL or BLU)>

For example Part Number (R9SSG) + Roll Size (495) + Colour Code (BLK) = R9SSG495BLK

All standard Pig's Tail Spiral Wrap sizes are available in:



Colour Code: BLK



Colour Code: YEL



Colour Code: RED



Colour Code: BLU

Part #	Hose OD Range (IN) _v	Spiral Wrap ID (IN)	Wall Thickness (IN)	Helix Band Width (IN)	To Fit Hydraulic Hose Size	Color	Feet Per Roll
R9SSG495-BLK	0.28 - 0.51	0.28	0.06	0.25	5/16"	Black	495
R12SSG100-BLK	0.39 - 0.66	0.4	0.06	0.4	3/8"	Black	100
R12SSG165-BLK	0.39 - 0.66	0.4	0.06	0.4	3/8"	Black	165
R12SSG165-BLU	0.39 - 0.66	0.4	0.06	0.4	3/8"	Blue	165

Essential components for industry

www.daemar.com



100% Virgin Polyethylene

- Excellent abrasion resistance and durability.
- Very flexible and durable
- Protects from -40°F to +280°F

User Friendly

- Beveled edges won't cut hose or user
- Wall thickness designed for easy installation
- Pitch designed to prevent leapfrogging
- Install without removing fittings
- Can cover only specific areas

Multiple Sizes

- Broad size range to wrap almost any hose.
- Larger sizes for bundling multiple hoses/cables
- Proper sizing prevents wrap from sliding on hose

R12SSG165-RED	0.39 - 0.66	0.4	0.06	0.4	3/8"	Red	165
R12SSG165-YEL	0.39 - 0.66	0.4	0.06	0.4	3/8"	Yellow	165
R16SSG66-BLK	0.47 - 0.86	0.45	0.06	0.48	1/2"	Black	66
R16SSG66-BLU	0.47 - 0.86	0.45	0.06	0.48	1/2"	Blue	66
R16SSG66-RED	0.47 - 0.86	0.45	0.06	0.48	1/2"	Red	66
R16SSG66-YEL	0.47 - 0.86	0.45	0.06	0.48	1/2"	Yellow	66
R16SSG100-BLK	0.47 - 0.86	0.45	0.06	0.48	1/2"	Black	100
R16SSG165-BLK	0.47 - 0.86	0.45	0.06	0.48	1/2"	Black	165
R20SSG66-BLK	0.62 - 1.06	0.55	0.07	0.57	5/8"	Black	66
R20SSG66-BLU	0.62 - 1.06	0.55	0.07	0.57	5/8"	Blue	66
R20SSG66-RED	0.62 - 1.06	0.55	0.07	0.57	5/8"	Red	66
R20SSG66-YEL	0.62 - 1.06	0.55	0.07	0.57	5/8"	Yellow	66
R20SSG100-BLK	0.62 - 1.06	0.55	0.07	0.57	5/8"	Black	100
R20SSG165-BLK	0.62 - 1.06	0.55	0.07	0.57	5/8"	Black	165
R25SSG66-BLK	0.86 - 1.37	0.8	0.08	0.82	15/16"	Black	66
R25SSG66-BLU	0.86 - 1.37	0.8	0.08	0.82	15/16"	Blue	66
R25SSG66-RED	0.86 - 1.37	0.8	0.08	0.82	15/16"	Red	66
R25SSG66-YEL	0.86 - 1.37	0.8	0.08	0.82	15/16"	Yellow	66
R25SSG100-BLK	0.86 - 1.37	0.8	0.08	0.82	15/16"	Black	100
R25SSG165-BLK	0.86 - 1.37	0.8	0.08	0.82	15/16"	Black	165
R32SSG66-BLK	1.06 - 1.69	1	0.09	0.94	1-1/8"	Black	66
R32SSG66-BLU	1.06 - 1.69	1	0.09	0.94	1-1/8"	Blue	66
R32SSG66-RED	1.06 - 1.69	1	0.09	0.94	1-1/8"	Red	66
R32SSG66-YEL	1.06 - 1.69	1	0.09	0.94	1-1/8"	Yellow	66

R32SSG100-BLK	1.06 - 1.69	1	0.09	0.94	1-1/8"	Black	100
R32SSG165-BLK	1.06 - 1.69	1	0.09	0.94	1-1/8"	Black	165
R40SSG66-BLK	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Black	66
R40SSG66-BLU	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Blue	66
R40SSG66-RED	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Red	66
R40SSG66-YEL	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Yellow	66
R40SSG100-BLK	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Black	100
R40SSG165-BLK	1.30 - 2.17	1.26	0.09	1.18	1-3/8"	Black	165
R50SSG66-BLK	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Black	66
R50SSG66-BLU	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Blue	66
R50SSG66-RED	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Red	66
R50SSG66-YEL	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Yellow	66
R50SSG100-BLK	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Black	100
R50SSG165-BLK	1.65 - 2.52	1.5	0.12	1.38	1-3/4"	Black	165
R63SSG66-BLK	2.05 - 2.95	2	0.14	1.57	2-1/4"	Black	66
R63SSG66-BLU	2.05 - 2.95	2	0.14	1.57	2-1/4"	Blue	66
R63SSG66-RED	2.05 - 2.95	2	0.14	1.57	2-1/4"	Red	66
R63SSG66-YEL	2.05 - 2.95	2	0.14	1.57	2-1/4"	Yellow	66
R63SSG100-BLK	2.05 - 2.95	2	0.14	1.57	2-1/4"	Black	100
R75SSG66-BLK	2.56 - 3.80	2.4	0.15	1.6	2-5/8"	Black	66
R75SSG66-BLU	2.56 - 3.80	2.4	0.15	1.6	2-5/8"	Blue	66
R75SSG66-RED	2.56 - 3.80	2.4	0.15	1.6	2-5/8"	Red	66
R75SSG66-YEL	2.56 - 3.80	2.4	0.15	1.6	2-5/8"	Yellow	66
R90SSG66-BLK	3.15 - 4.30	2.83	0.18	1.78	3"	Black	66



R90SSG66-BLU	3.15 - 4.30	2.83	0.18	1.78	3"	Blue	66
R90SSG66-RED	3.15 - 4.30	2.83	0.18	1.78	3"	Red	66
R90SSG66-YEL	3.15 - 4.30	2.83	0.18	1.78	3"	Yellow	66
R110SSG40-BLK	3.80 - 4.90	3.43	0.22	2.17	3-7/8"	Black	40
R110SSG40-BLU	3.80 - 4.90	3.43	0.22	2.17	3-7/8"	Blue	40
R110SSG40-RED	3.80 - 4.90	3.43	0.22	2.17	3-7/8"	Red	40
R110SSG40-YEL	3.80 - 4.90	3.43	0.22	2.17	3-7/8"	Yellow	40
R125SSG40-BLK	4.50 - 5.50	4.48	0.22	2.17	4"	Black	40
R125SSG40-YEL	4.50 - 5.50	4.48	0.22	2.17	4"	Yellow	40
R140SSG27-BLK	4.80 - 6.00	5.07	0.22	2.17	4-1/2"	Black	27
R140SSG27-YEL	4.80 - 6.00	5.07	0.22	2.17	4-1/2"	Yellow	27
R160SSG20-BLK	5.70 - 7.00+	5.87	0.22	2.36	5"	Black	20
R160SSG20-YEL	5.70 - 7.00+	5.87	0.22	2.36	5"	Yellow	20

Essential components for industry

www.daemar.com